

10/130 Precision Matched Passive Double Clad Fibers for 2 Micron



These Coherent precision matched passive double-clad fibers feature a 10 μm core diameter and a 130 μm clad diameter and are optimized to match Coherent's active Tm-doped 10P/130 fibers. This precise matching allows for the lowest splice loss, improving performance for all applications, including low to mid-power CW and pulsed fiber lasers and amplifiers operating in the 2 μm wavelength range. The small core, 0.15 NA fiber facilitates low bend loss and highly efficient single-mode operation while the telecom-like 130 μm cladding diameter makes handling, including cleaving and splicing, as simple as possible.

Typical Applications

- Low to mid power CW and pulsed Eye Safe 2 μm lasers & amplifiers
- Eye Safe industrial & medical lasers
- Military and commercial LIDAR

Features & Benefits

- NuCOATTM fluoroacrylate coating — Greater fiber durability in extreme environmental operating & storage conditions
- Robust single-mode core at ~2 μm — Easy to maintain single-mode LP01 beam through fiber and components
- PANDA-style stress structure for increased birefringence — Superior optical performance
- All fiber proof tested to > 100 kpsi — Critical for ensuring long term reliability when coiling
- Tight geometric tolerances — Excellent lot to lot uniformity

Optical Specifications

Operating Wavelength
Core NA
First Cladding NA (5%)
Cladding Attenuation
Birefringence

SM-GDF-10/130-15M

800 – 2100 nm
0.150 $\pm$ 0.010
 $\geq$ 0.460
 $\leq$ 15.0 dB/km @ 1095 nm
N/A

PM-GDF-10/130-2000-M

800 – 2100 nm
0.150
 $\geq$ 0.460
 $\leq$ 15.0 dB/km @ 1095 nm
nominal 1.5×10^{-4}

Geometrical & Mechanical Specifications

Cladding Diameter
Core Diameter
Coating Diameter
Coating Concentricity
Core/Clad Offset
Clad Non-Circularity
Coating Material
Proof test Level

130.0 $\pm$ 1.0 μm
10.0 $\pm$ 1.0 μm
215.0 $\pm$ 10.0 μm
< 5.0 μm
 $\leq$ 0.70 μm
 $\leq$ 0.5 %
Low Index Acrylate
 $\geq$ 100 kpsi (0.7 GN/m²)

130.0 $\pm$ 1.0 μm
10.0 $\pm$ 1.0 μm
245.0 $\pm$ 10.0 μm
< 5.0 μm
 $\leq$ 0.70 μm
N/A
Low Index Acrylate
 $\geq$ 100 kpsi (0.7 GN/m²)



Nufern • 7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • Email: tech.sales@coherent.com
www.coherent.com ; www.shop.coherent.com • Coherent products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Coherent can assist with your requirements.

NU0173- 11/12/2020